

WIRED BOUNDARY LINE MICROPHONE SYSTEM



Microphone unit

- ✦ Frequency response: 40Hz-16KHz
- ✦ Sensitivity: -44 dB±2dB
- ✦ Reference sound receiving distance: 20~120cm
- ✦ The system power supply for all the Microphones is provided by the main unit.
- ✦ Its connected with 8-PIN T-type hand-in-hand loop in loop out cable.
- ✦ Microphone type - Electric capacity
- ✦ The LED red indicator lamp shows the status of the microphone.
- ✦ The chairman unit number in the system is unrestricted, can join in any position of the system.
- ✦ Chairman can Mute delegate MIC by priority button,
- ✦ Indicative sound for chairman unit (optional)

TECHNICAL DATA

Model	Microphone unit 100CUBL/100DUBL
Voltage	DC18V (Supply by 8PIN cable)
Power consumption	1W
T.H.D.	<0.05%
Dimension	120(L) mm x 85mm (W) x 20mm(H)
Sensitivity	-44dB ±2dB
Frequency response	100Hz—16KHz
Color	Black
Installation	Tabletop

MICROPHONE UNIT CONSIST OF

- ✦ Unidirectional MIC
- ✦ Annular red indicator lamp
- ✦ ON/OFF button
- ✦ Priority button. Chairman unit can turn down delegate MIC by pressing the priority button.



MADE IN INDIA

WIRED BOUNDARY LINE MICROPHONE SYSTEM



1000 CMU

Microphone Controller

- + 256 Microphones can work in a single room.
- + Audio controller support 64units- Chairman & Delegate.
- + To connect more than 64 Microphones, Extension Power Unit is required.
- + It supports discuss mode, work mode, Free mode, Limit 1/2/3/5
- + Port for Telephone interface input- Telephone meeting compatible.
- + Connection:
 - a. 1 pc 13m main cable with 8PIN plugs;
 - b. 8 PIN socket for system connection.

Audio Controller main unit consists of

- + Power switch
- + Power LED
- + Mode: Limit 1/2/3/5, Free
- + TREBLE
- + MEDIANT
- + BASS
- + System volume (MASTER)
- + System Line 1, 2, 3, EXT
- + LINE OUT
- + MIX OUT
- + TEL IN/OUT
- + Data port for connection video processor
- + Power AC 220V/50Hz

TECHNICAL DATA

Model Data	1000CMU
Power Supply	AC110V~220V; 50/ 60Hz
Power Consumption	115W
T.H.D.	<0.05%
Dimension	480X340X45mm
Sensitivity	-56dB Wire microphone
Frequency response	40Hz—16KHz
Net Weight	5Kg
Color	Black
Installation	19-inch frame

Extension Power supply unit consists of

- + Power on/off
- + Power indicator
- + EXPAND INPUT (IN: To the previous main unit or extension power supply, EXT: to the next extension power unit)
- + EXPAND OUTPUT: Six output line for connect microphone, and each line with power control.
- + Power AC 220V/50Hz.



GeM Government e Marketplace



TEAM INFOVISION PVT. LTD.

17 Upper Ground Floor, DLF Industrial Area, Moti Nagar, New Delhi-110015

+91-9810161282, 9810187450

info@teaminfovision.com www.teaminfovision.com

GSTIN No. : 07AABCT7526N1ZW

MSME No. : UAM DL03A000567

CIN No. U31909DL2001PTC112594